

HD21

Customer Interface Unit

HD21 is a customer interface unit designed for simplicity and user-friendliness. Shaped in a mobile phone form factor, it gives user the familiarity of a 3 x 4 keypad that is smooth to the touch and ease of one hand operation. HD21 is equipped with comprehensive functions like topping up credits via STS, reading household's instantaneous energy consumption, identifying alarm indicators on LCD, buzzer on low credit and many more.



Key Features



STS
COMPLIANT



MULTIPLE
ALARM INDICATOR



DISPLAY VARIANCE



AUTO RECONNECT

HD21

Customer Interface Unit



Weight: 76g (without battery)

Supported Meter Types

- Mk32
- Mk7MDC
- Mk10M*

Communications

- Radio Frequency
 - Open air communication distance <100m
 - Frequency Bands: 433MHz
 - Transmit Power: 20 dBm
- Voltage & Power Supply Type
 - 3V DC (2xAAA non-rechargeable batteries) or 5V DC (Micro USB connector)

Physical Display

- 7 characters of seven-segment display with backlight
- 8mm x 3mm

Display

- Dimensions of 45.7mm x 17mm
- LCD Viewing angle: +/-30 degree (Left-Right) +10/-20 degree (up-down)
- LED Indicators: 3 x LEDs

Alarm

- Buzzer


Keypad

- Silicone keypad

Environmental

- Specified operating range:
 - 10°C to +60°C
- Operating limit range:
 - 25°C to +65°C
- Storage range limit:
 - 25°C to +70°C
- Relative humidity:
 - Up to 95% non-condensing
- Ingress protection: IP54

LCD Display



- 1 Signal Strength
- 2 Page Indicator
- 3 Low Credit
- 4 Credit OK
- 5 Meter Relay Status
- 6 Meter Program Key Indicator
- 7 CIU Battery Indicator
- 8 Magnetic Detection
- 9 Meter Lid Cover Tamper
- 10 Meter Terminal Cover Tamper
- 11 Overload
- 12 Unbalanced Load
- 13 Reverse Power
- 14 CIU Connection Status

* Under Development

EDMI Limited (Headquarters)

47 Yishun Industrial Park A, Singapore 768724
Tel: +65 6756 2938 Fax: +65 6756 0125
Email: marketing@edmi-meters.com
techsupport@edmi-meters.com

www.edmi-meters.com

