

Mk32

ABACUS – Class 1 and Class 2

Advanced Single Phase Meter

Designed for residential use, Mk32 is a single phase meter with integrated 100A UC3 compliant relays. It is able to operate in either STS compliant prepaid mode or post-paid mode. Mk32 can operate with the EDM I CIU (Customer Interface Unit) - HD18 and HD21 wirelessly as a split meter.



Key Features



STS
COMPLIANT



DISCONNECT
RELAY



ANTI TAMPER



FIRMWARE
UPGRADE



RF WIRELESS
TRANSCIVER



NEUTRAL CURRENT
MEASUREMENT

Mk32

ABACUS - Class 1 and Class 2

Advanced Single Phase Meter



Standards and Compliance

- Class 1 and Class 2
- IEC 62052-11, 62053-21, 62053-23, 62055-31, 62055-41, 62055-15

Measurement

- 1 phase 2 wire (optional neutral current measurement)

Voltage

- Nominal voltage: 220V - 240V
- Operating range: 0.5Un to 1.2Un
- Withstand range: 0V to 456V
- Impulse voltage: 4kV

Current

- WC range: 5/60A, 10/60A, 5/100A, 10/100A
- WC limit: 30 times Imax for 0.5 cycles
- Phase current measurement sensor: Shunt
- Neutral current measurement sensor: CT

Terminal

- Terminal cross-section: 58.24mm²

Power Consumption

- Voltage circuit: <10VA/phase, 2W @ Vn
- Current circuit: <2.5VA/phase @ In

Frequency

- 50Hz/60Hz

Inputs/Outputs Configuration

- Up to 5 x LED indicators
- Up to 2 x outputs

Relay

- Up to two internal disconnect relays (80A or 120A)

Battery

- Internal lithium battery (3.6V)
- Internal super capacitor
- Backup time: 5 years without power (lithium battery)
- Backup time: 48 hours without power (super capacitor)

Data Memory

- 2MB of non-volatile memory

Display

- 8 Character of eight-segment display (9mm x 4.96mm)
- Display available without mains power
- Option for backlight

Keypad

- Option of silicone keypad

Real-time Clock

- Precision clock accuracy: <5ppm (15 seconds per month) at 23°C

Measured Values

- 1 element 4 quadrants
- Import/Export/Absolute Wh and varh
- Per quadrant Wh and varh
- W, var, VA, Vrms, Irms
- Power factor, frequency

Load Survey/Profile

- Up to 8 channels and 2 independent surveys
- Intervals programmable from 1 to 60 minutes
- Energy, instantaneous readings, pulsing inputs as channel sources
- Ability to store average/minimum/maximum values for interval duration

Time of Use

- Up to 8 rates plus unified rate
- Up to 8 separate import and export registers
- Daily, weekly, monthly, yearly and special days
- Up to 48 previous periods plus period totals
- Block maximum demand
- Time of maximum demand

Calendar

- Supports Daylight Saving Time

Tamper Detection and Alarms

- Provision for sealing with conventional wire or plastic seals
- Ultrasonic welding option for lid cover and base assembly
- Reverse current detection

- Line and neutral current unbalance detection
- Meter cover and terminal cover detection
- Faulty load relay detection
- Overload detection
- Magnetic tamper detection (optional)
- Alarms are stored in event logs

Security

- Multi-level security (username and password including encrypted log-in)
- Up to 10 independent security levels
- Up to 8 individual users

Operation Mode

- Postpaid/Prepaid

Communications

- Up to 3 independently working communication ports:
 - Optical port: FLAG (IEC 62056-21)
- Built-in communication
 - RF: 300MHz to 950MHz (configurable)
 - RS-485 screw terminal (2-wire)

Protocol

- EDML command line

Environmental

- Specified operating range:
 - 25°C to +55°C
- Operating range limit:
 - 40°C to +70°C
- Storage range limit:
 - 40°C to +85°C
- Relative humidity:
 - Up to 75% mean, 95% non-condensing for 30 days
- Ingress protection: IP54 (without suction)

EDMI Limited (Singapore)

47 Yishun Industrial Park A,
Singapore 768724

EDMI Pty Ltd (Australia)

Level 7, 51 Alfred Street,
Fortitude Valley, Queensland
Australia 4006

EDMI Europe Limited (United Kingdom)

Form 1, 17 Barley Wood
Business Park, Bartley Way,
Hook, Hampshire RG27
9AXA, United Kingdom

EDMI America Inc. (USA)

One City Plaza, Suite 1301,
421 Fayetteville Street,
Raleigh, North Carolina,
27601 United States

www.edmi-meters.com



Visit our website at www.edmi-meters.com to find our other locations.

Copyright © 2025 EDMl Group. All Rights Reserved. All trademarks are the property of their respective holders. EDMl Group continuously develops its products and solutions and reserves the right to modify specifications contained herein without notice.