

Mk10D

ATLAS – Class 1 and Class 2

Three Phase Smart Meter with
Disconnect Feature

Built on the advanced Atlas metering platform,
the Mk10D adds three 100A UC3 compliant relays
into the meter which allows for disconnection and
reconnection of electrical services remotely.



Key Features

AMI

AMI READY



DISCONNECT
RELAY



MULTIPLE COMMS
OPTIONS



LARGE LCD
DISPLAY



MEASURE
EVERYTHING



UPGRADEABLE



ANTI TAMPER



LARGE DATA
STORAGE

Mk10D

ATLAS - Class 1 and Class 2

Three Phase Smart Meter with Disconnect Feature



Standards and Compliance

- Class 1 and Class 2
- IEC 62052-11, 62052-21, 62053-21, 62052-31, 62053-23, 62059-32-1
- AS 62052.11, 62052.21, 62053.21, 62053.23, 62052.31, 62054-21
- NMI M6

Measurement

- 1 phase 2 wire ^
- 3 phase 4 wire
- Option for neutral current measurement

Voltage

- Nominal voltage: 120V^{*}, 220V – 240V
- Operating range: 110V – 130V^{*}, 176V – 276V
- Withstand: 1Dx3- Up to 456V
- Burden: IEC 62053-21/23 compliant

Current

- WC range: 5/100A, 10/100A
- WC Limit: 7000A for 3 cycles
- Burden: <0.5VA/phase
- Overload Current: 128A

Frequency

- 50Hz ± 6%

Relay

- 100A supply control switch; IEC 602055-31 Annex C U3
- 63.5A load control switch; IEC 62055-31 Annex UC3 and IEC 62052-21
- Post-relay voltage detection - hardware capable
- Option for individual supply switching at 100A
- Enhanced relay switching time ≤10s
- May be ordered without disconnect relays

Inputs/Outputs Configuration

- Up to 4 independently isolated I/O
- Options include: Passive/Active inputs, S0/BOSFET/Relay outputs
- Passive input voltage: 5V, 12V, 48V, 110V, 240V
- Active input voltage: 14Vdc (common ground)
- S0 Output: 27V, 27mA maximum
- BOSFET output: 240V, 100mA
- Relay output: 240V, 2A
- 2 Programmable LED indicators
- Programmable output pulse width: 1ms to 100ms

Battery

- Internal battery
- Option for external battery
- Option for additional supercap (72 hours)
- Backup time of 10 years without power (Lithium Battery)

Real-time Clock

- Accuracy (internal) within 15 seconds per month at 23°C
- Internal clock or line synchronisation

Data Memory

- 4.2 MB of non-volatile memory

Display

- Large 14 segment (starburst) alphanumeric display with 10.5mm x 5.1mm digit size
- 8 digit numerical value field and 6 digit description field
- Up to 60 user-defined screens of any meter parameter
- Definable enunciators
- Display available without main power
- LED backlight option

Measured Values

- 3 elements 4 quadrants
- Import/Export/Absolute Wh, varh and VAh
- Fundamental Wh
- Per quadrant Wh, varh and VAh
- Phase A,B,C and Total
- W, var, VA, Vrms, Irms
- Power factor, frequency, phasor angles
- Supports ripple control/AFLC

Power Quality Indication

- Total Harmonic Distortion (THD)
- Unbalance (sequence components)
- Option for live waveform display
- Sag/Swell
- -5 Cycle resolution
- -Records time/date/phase/duration/average and worst excursion
- -Programmable trigger levels

Load Survey/Profile

- Over 10,000 days storage (2 channels, 30-minute intervals)
- Supports Advanced Demand Management (ADM) with prioritised rules
- Up to 32 channels and 4 independent surveys
- Intervals programmable from 1 to 60 minutes
- Energy, instantaneous readings, pulsing inputs as channel sources
- Ability to store average/minimum/maximum values for interval duration

Time of Use

- Up to 8 rates plus unified rate
- Up to 32 separate import and export registers
- Daily, weekly, monthly, yearly and special days
- Up to 200 programmable special days

- Up to 61 previous billing periods plus billing totals
- Block or rolling maximum demand
- Time of maximum demand
- Energy, pulsing inputs

Calendar

- Supports Daylight Saving time
- Supports Gregorian or Persian calendars

Tamper Detection and Alarms

- Provision for sealing with conventional wire or plastic seals
- Bypassing current and reverse current detection
- Advanced tamper detection and logging
- Pre-programmed alarms for meter self-check
- Alarms trigger LEDs, enunciators, relay outputs or communications event
- Alarms are stored in event logs
- Configurable threshold; 3D magnetic tamper detection
- Source impedance monitoring

Security

- Multi-level security (username and password including encrypted log-in)
- Up to 7 independent security levels
- Up to 6 individual users
- AES128 bit encryption

Communications

- Up to 3 independently working communication ports:
 - Optical port: FLAG (IEC 62056-21) or ANSI Type 2 (ANSI C12.18)

- RS-232 with modem power supply (compatible with the majority of modems in the market)
- RS-485 multi-drop (2 or 4-wire RJ45 or 2-wire screw terminal)
- Compatible with MV-90™

Protocol

- EDI command line
- DLMS
- MODBUS

Software

- EDI AMI 2.0 (Storm)
- EDI Storm mobile software available for meter programming and reading
- EDI Energy Cloud software available for large scale AMI and AMR solutions
- Supported by many popular third-party multi-vendor AMR systems
- Supports Function Based Setup

Environmental

- Specified operating range: -25°C to +60°C
- Limit range of operation: -40°C to +70°C
- Storage range limit: -40°C to +80°C
- Relative humidity: Up to 75% mean, 95% non-condensing for 30 days
- Ingress protection: IP54

Safety

- Protective Class II
- Surge Test: 5kV
- Impulse Test: 12kV

Specifications with * symbol available on request. No Type Test reports; ^ symbol is tested to IEC and AS 62052-21/23.

EDMI Limited (Singapore)

47 Yishun Industrial Park A,
Singapore 768724

EDMI Pty Ltd (Australia)

Level 7, 51 Alfred Street,
Fortitude Valley, Queensland
Australia 4006

EDMI Europe Limited (United Kingdom)

Form 1, 17 Barley Wood
Business Park, Bartley Way,
Hook, Hampshire RG27
9AXA, United Kingdom

EDMI America Inc. (USA)

One City Plaza, Suite 1301,
421 Fayetteville Street,
Raleigh, North Carolina,
27601 United States

www.edmi-meters.com



Visit our website at www.edmi-meters.com to find our other locations.

Copyright © 2025 EDMi Group. All Rights Reserved. All trademarks are the property of their respective holders. EDMi Group continuously develops its products and solutions and reserves the right to modify specifications contained herein without notice.